

ETS SCHAEFER CORPORATION

MATERIAL SAFETY DATA SHEET

Date Prepared: 08/16/01

Revised/Reviewed: 08/16/01

1. PRODUCT AND COMPANY IDENTIFICATION

Name: Endoflex Sealant (Firestop Compound)

Class: Filled Acrylic Emulsion

HMIS:

H F R PP

1 O O B

Manufacturer/Supplier: ETS SCHAEFER CORPORATION
8050 HIGHLAND POINTE PARKWAY
MACEDONIA, OHIO 44056

Product Stewardship Program: Phone: (800) 863-5400 Fax: (330) 468-6610

2. HAZARDOUS INGREDIENT INFORMATION

<u>Ingredient</u>	<u>CAS #</u>	<u>% by Weight</u>	<u>Occupational Exposure</u>	<u>Vapor Pressure mm Hg @</u>
			<u>Limits</u>	<u>Temp.</u>
Not Applicable	N/A	N/A	N/A	N/A

1. This product does not contain any hazardous material(s) as defined by OSHA, 29 CFR 1910, 1200.
2. This product does not contain a chemical which is listed in Section 313 above de minimic concentration.

3. PHYSICAL DATA

Boiling Range: 212°F (100°C)
Vapor Density: (AIR=1)>1
VOCS: 5.40 g/l
Evaporation Rate: (H20=1) 1
% Volatile By Volume: 32.0
Wgt./Gal: 10+0.5lbs./Gal.
Appearance and Odor: Red, Mild Latex Odor
Solubility in Water: Appreciable

MATERIAL SAFETY DATA SHEET

Date Prepared: 8/16/01

Revised/Reviewed: 08/16/01

4. FIRE & EXPLOSION HAZARD DATA

Flammability Classification:

Flash Point: None (water base compound)

LEL: Not Applicable (N/A)

UEL: N/A

Extinguishing Media: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog

Unusual Fire & Explosion Hazards: This product will not burn, but may spatter if the temperature exceeds the boiling point. Dry film may burn in an intense fire.

Special Firefighting Procedures: Self contained breathing apparatus should be used in enclosed areas.

5. HEALTH HAZARD DATA

Effects of Overexposure

Eyes: May cause irritation

Skin: Excessive exposure may cause drying and chapping.

Inhalation: May cause gagging, nausea and upper respiratory distress

Ingestion: Possible nausea

Medical Conditions Prone To Aggravation by Exposure: None Known

Primary Route(s) of Entry: Dermal, Inhalation, Ingestion

Emergency and First Air Procedures

Eyes: Flush with water for 15 minutes. Do not rub. Consult physician if irritation persists.

Skin: Wash with mild soap and water

Inhalation: Remove to fresh air

Ingestion: Induce vomiting. Consult Physician

Chemical listed as a carcinogen or potential carcinogen: NTP: No OSHA: No
IARC: No

MATERIAL SAFETY DATA SHEET

Date Prepared: 8/16/01

Revised/Reviewed: 08/16/01

6. REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: Carbon Monoxide, Carbon dioxide. Trace amounts of Nitrogen and asphyxiants.

Conditions to Avoid: Strong Acids and Strong Alkali.

Incompatibility (material to avoid): Strong Acids and Alkali.

7. SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Keep all spectators away. Uncontaminated material may be recovered and reused. If contaminated scoop into receptacle for disposal.

Waste Disposal Method: Allow material dry. Dispose in accordance with federal, state, and local regulations.

8. SAFE HANDLING & USE INFORMATION

Respiratory Protection: Use MSHA/NIOSH approved respirator in poorly ventilated areas.

Ventilation: General (mechanical) room ventilation is to be satisfactory for normal usage.

Protective Gloves: Impervious

Eye Protection: Safety Glasses or goggles

Other Protective Equipment: As needed

Hygienic Practices: Avoid contact with skin and clothing. Wash after handling and launder contaminated clothing before reuse.

MATERIAL SAFETY DATA SHEET

Date Prepared: 8/16/01

Revised/Reviewed: 08/16/01

9. SPECIAL PRECAUTIONS

Precautions to be taken in Handling & Storage: Seal container when not in use. Store in well ventilated area below 90° F (33°C).

Other Precautions: The information and recommendations offered herein, are for the users consideration and examination and is to be used in addition to all other information that is available and pertinent. It is the users responsibility to determine the suitability of its specific and particular use.

Important Note: This information references the product itself, not in combination with any other material to which may eventually be applied or come in contact with. The user must determine any local, state or federal regulations regarding the use and disposal of this product in conjunction with other materials which may be regulated (For example: Asbestos or asbestos containing materials).